

Wall mounted unit

FTXB-C



Econo mode



Energy saving during standby mode



Comfort mode



Vertical auto swing

Wall mounted unit for low energy consumption and pleasant comfort

- › Seasonal efficiency values up to A+
- › Flat, stylish front panel blends easily within any interior décor and is more easy to clean
- › The infrared remote control is user friendly and equipped with a timer function that enables you to programme the unit to start or stop at your desired time.
- › Vertical auto swing moves the discharge flaps up and down for efficient air and temperature distribution throughout the room
- › 24 hour timer can be set to start heating or cooling anytime during a 24 hour period

FTXB-C + RXB-C



| Indoor unit | | FTXB | 20C | 25C | 35C | 50C | 60C | |
|----------------------|-------------------------|---|-------------|---------------|---------------|---------------|----------------|----------------|
| Casing | Colour | | White | | | | | |
| Dimensions | Unit | HeightxWidthxDepth | 283x770x216 | | | 310x1,065x224 | | |
| Sound power level | Cooling/Heating | | 55/55 | | 58/58 | 55 | 61 | |
| Sound pressure level | Cooling | Super high/High/Nom./Low/Silent operation | dBA | -/39/33/25/21 | -/40/33/26/21 | -/41/34/27/23 | 44/40/38/35/32 | 46/43/41/37/33 |
| | Heating | Super high/High/Nom./Low/Silent operation | dBA | -/39/34/28/25 | -/40/34/28/25 | -/41/35/29/26 | 44/40/38/35/32 | 46/43/41/37/33 |
| Control systems | Infrared remote control | | ARC470A1 | | | | - | |


| Efficiency data | | FTXB + RXB | 20C + 20C | 25C + 25C | 35C + 35C | 50C + 50C | 60C + 60C | |
|--|---------------------------|---------------------------|-------------|-------------------|-------------------|-------------------|-------------------|-------------------|
| Cooling capacity | Min./Nom./Max. | kW | 1.3/2.0/2.6 | 1.3/2.5/3.0 | 1.3/3.3/3.8 | 1.630/5.480/6.200 | 1.750/6.230/6.500 | |
| Heating capacity | Min./Nom./Max. | kW | 1.3/2.5/3.5 | 1.3/2.8/4.0 | 1.3/3.5/4.8 | 1.170/5.620/6.600 | 1.200/6.400/7.100 | |
| Power input | Cooling | Min./Nom./Max. | kW | 0.310/0.510/0.720 | 0.310/0.770/1.050 | 0.290/1.030/1.300 | 0.280/1.700/1.910 | 0.280/1.931/2.000 |
| | Heating | Min./Nom./Max. | kW | 0.250/0.600/0.950 | 0.250/0.700/1.110 | 0.290/0.940/1.290 | 0.240/1.500/1.880 | 0.240/1.680/2.000 |
| Seasonal efficiency (according to EN14825) | Cooling | Energy label | | A+ | | | | |
| | | Pdesign | kW | 2.00 | 2.50 | 3.30 | 5.48 | 6.23 |
| | | SEER | | 5.98 | 6.02 | 6.05 | 5.93 | 6.09 |
| | | Annual energy consumption | kWh | 117 | 145 | 191 | 324 | 359 |
| | Heating (Average climate) | Energy label | | A+ | | | | |
| | Pdesign | kW | 2.20 | 2.40 | 2.80 | 3.64 | 3.80 | |
| | SCOP | | 4.10 | 4.01 | 4.06 | 4.27 | 4.06 | |
| | Annual energy consumption | kWh | 751 | 838 | 966 | 1,195 | 1,311 | |
| Nominal efficiency | EER | | 3.94 | 3.25 | 3.21 | 3.22 | 3.23 | |
| | COP | | 4.19 | 4.01 | 3.71 | 3.75 | 3.81 | |
| | Annual energy consumption | kWh | 254 | 385 | 514 | 851 | 964 | |
| | Energy label | Cooling/Heating | | A/A | | | | |

| Outdoor unit | | RXB | 20C | 25C | 35C | 50C | 60C |
|----------------------|-------------------------|------------------------|----------------|-----|---------|-------------|--------|
| Dimensions | Unit | HeightxWidthxDepth | 550x658x275 | | | 753x855x328 | |
| Sound power level | Cooling | | 60 | | 62 | 64 | 65 |
| | Heating | | 61 | | 62 | 64 | 65 |
| Sound pressure level | Cooling | High/Nom. | dBA | | 46/- | 48/- | -/51 |
| | Heating | High/Nom. | dBA | | 47/- | 48/- | -/51 |
| Operation range | Cooling | Ambient Min.-Max. | °CDB | | | | -10~46 |
| | Heating | Ambient Min.-Max. | °CWB | | | | -15~18 |
| Refrigerant | Type/GWP | | R-410A/2,087.5 | | | | |
| | Charge | kg/TCO ₂ eq | 0.74/1.5 | | 1.0/2.1 | 1.45/3.0 | |
| Power supply | Phase/Frequency/Voltage | Hz/V | 1~/50/220-240 | | | | |

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-027

03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.